Moderra concrete • siding

Project Estimate Sheet - Moderra (Siding)

Name _____ **Phone** _____

Address _____ **Fax** _____

I. General Information

Wall Lineal Feet: _____ Wall Height: _____ Outside Corners: _____

1. Is the total Wall Height divisible by 8"? (Yes / No) **2.** Are you going to use Sill Units? (Yes / No)

*If **1** and **2** are both "No" or both "Yes", then 4" Blocks are needed to achieve desired height*

II. 8" Courses

_____ Wall Height (in.) minus 4" (if 4" Blocks needed)

& minus 4" (if 4" Sills needed) = _____ Moderra Height

_____ Moderra Height ÷ 8

= _____ **8" Courses**

III. 8" Block

_____ Wall Lineal Feet x 12" = _____ ÷ 16" = _____ 8" Blocks per Course

_____ 8" Blocks per Course x _____ 8" Courses = _____ 8" Blocks

_____ **8" Blocks**

IV. 8" Corner

_____ 8" Courses x _____ Outside Corners = _____ 8" Corners

_____ **8" Corners**

V. 4" Block

_____ Wall Lineal Feet x 12" = _____ ÷ 16" = _____ 4" Blocks

_____ **4" Blocks**

VI. 4" Corner

(Necessary if using 4" block)

_____ Outside Corners = _____ 4" Corners

_____ **4" Corners**

VII. 4" Sill

(Optional)

_____ Wall Lineal Feet x 12" = _____ ÷ 16" = _____ 4" Sills

_____ **4" Sills**

VIII. Trim Channel*

**Heights should be figured to the top of the Moderra only.*

***Only use if Corner Block is not used.*

_____ Door Height (in.) x 2 = _____

_____ Window Height (in.) x 2 = _____

_____ Inside Corners Height (in.) x 2 = _____

_____ Outside Corners Height (in.)** = _____

Total Height = _____

_____ Total Height ÷12"÷ 8'

= _____ **Trim Channels**

IX. H-Channel

_____ 8" Blocks x 8" = _____

_____ 8" Corners x 8" = _____

_____ 4" Blocks x 4" = _____

_____ 4" Corners x 4" = _____

Total Height = _____

_____ Total Height ÷12"÷ 8'

= _____ **H-Channels**

X. Starter Ledge

(Pre-drilled Steel)

_____ Wall Lineal Feet ÷ 10'

= _____ **Starter Ledges**

XI. Super-Stik

_____ Wall Lineal Feet ÷ 20'

= _____ **Super-Stik Tubes**

XII. Screws

(1-1/2" Post Frame)

_____ Trim Channels + _____ H-Channels

x 4 = _____ **Screws**

XIII. Lag Screws

(3/8" x 2" & Washers)

_____ Starter Ledges x 7

= _____ **Lag Screws & Washers**

Moderra Components (Siding)

8" Block
8"H x 16"W x 2.5"D
25 lbs.
0.889 sq. ft.

8" Corner Block
8"H x 8"W x 2.5"D
22 lbs.
0.889 sq. ft.

4" Block
4"H x 16"W x 2.5"D
12 lbs.
0.445 sq.ft.

4" Corner Block
4"H x 8"W x 2.5"D
11 lbs.
0.445 sq. ft.

4" Sill Block
4"H x 16"W x 4.5"D
18 lbs.
0.445 sq. ft.

H-Channel
Aluminum
4.32 lbs.
8 feet

Trim-Channel
Aluminum
3.16 lbs.
8 feet



Starter Ledge
2"H x 3"W x .25"D
41 lbs.
10 feet

Super-Stik™
29 oz.